

XML API SPECIFICATIONS

(Version:3.3.0)

Send SMS XML API :

http://sms.####.com/xml-api.php?xml=<Your XML_data>&format=XML';

Parameter Specifications : -

```
<?xml version="1.0" encoding="UTF-8"?>
  <api>
    <username>XXXX</username>
    <password>XXXX</password>
    <senderid>XXXX</senderid>
    <route>1</route>
    <datetime>2016-12-06 04:45pm</datetime>
    <unicode></unicode>
    <message><![CDATA[demo msg]]></message>
    <sms>
      <to>99XXXXXXXX</to>
    </sms>
    <sms>
      <to>88XXXXXXXX</to>
    </sms>
    <sms>
      <to>84XXXXXXXX</to>
    </sms>
  </api>
```

Parameters & Descriptions :

- **username** : Username of the Account. (Required)
- **password** : Password of the Account. (Required)
- **SenderId** : Enter your 6char-senderid.(Required)
- **route** : 1 for Transactional Gateway(Required)
- **number** : Enter multiple numbers by comma separated.(Required)
- **message** : Your msg content.(Required)
- **datetime** : for schedule sms. (Optional)
- **Unicode** : 2 (if you want to send regional language msg then use otherwise not required to use this parameter). (Optional)
- **Format** : Response format type.(Required)
- **sms** : SMS Node(can repeat).(Required)
- **to** : Mobile number in sms node.(Required)

Error Status :

```
<?xml version='1.0' encoding='UTF-8'?>  
  
  <api>  
  
    <status>Error</status>  
  
    <message>Error description will here.</message>  
  
  </api>
```

Success Status :

```
<?xml version='1.0' encoding='UTF-8'?>
  <api>
    <status>Success</status>
    <data>
      <msgid>Message id will generate here</msgid>
    </data>
    <message>Message Submitted Successfully</message>
  </api>
```

Sample code in php :

```
<api>
  <username>XXXX</username>
  <password>XXXX</password>
  <senderid>XXXX</senderid>
  <route>1</route>
  <datetime>2016-12-06 04:45pm</datetime>
  <unicode></unicode>
  <message><![CDATA[demo msg]]></message>
  <sms>
    <to>99XXXXXXXX</to>
  </sms>
  <sms>
    <to>88XXXXXXXX</to>
  </sms>
```

```
<sms>
  <to>84XXXXXXXX</to>
</sms>
</api>';
$api_url = http://sms.#####.com /xml-api.php?xml='.urlencode($xmldata).'&format=XML';
$response = file_get_contents($api_url);
print_r($response);
```

Delivery Report Check XML API :

<http://sms.#####.com/xml-dlr.php?xml=<Your XML data>&format=XML'>

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<api>
```

```
<username>XXXXX</username>
```

```
<password>XXXXX</password>
```

```
<msgid>XXXXX</msgid>
```

```
</api>
```

- username : Username of the Account.
- password : Password of the Account.
- msgid : Pass the msgid which you got at the moment of msg submission

Error Status :

```
<?xml version='1.0' encoding='UTF-8'?>
```

```
<api>
```

```
<status>Error</status>
```

```
<message>Error description will here.</message>
</api>
```

Success Status :

```
<?xml version='1.0' encoding='UTF-8'?>
<api>
  <sms>
    <mobile>91XXXXXXXXXX</mobile>
    <status> Delivered </status>
  </sms>
  <sms>
    <mobile>91XXXXXXXXXX </mobile>
    <status>Submitted</status>
  </sms><sms>
    <mobile>91XXXXXXXXXX </mobile>
    <status> Absent Subscriber </status>
  </sms>
</api>
```

Delivery Report Code :

- 1 - Delivered
- 2 - Submitted
- 3 - Rejected
- 4 - Absent Subscriber
- 5 - Failed

Balance Check XML API :

http://sms.####.com/xml-credit.php?xml=<Your XML_data>&format=XML'

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<api>
```

```
<username>XXXXX</username>
```

```
<password>XXXXX</password>
```

```
< route>XXXXX</ route>
```

```
</api>
```

- username : Username of the Account.
- password : Password of the Account.
- route: Gateway Id.(Required)

Error Status :

```
<?xml version='1.0' encoding='UTF-8'?>
```

```
<api>
```

```
<status>Error</status>
```

```
<message>Error description will here.</message>
```

```
</api>
```

Success Status :

```
<?xml version='1.0' encoding='UTF-8'?>
```

```
<api>
```

```
<status>Success</status>
```

```
<balance>XXXXX</balance>
```

```
</api>
```